

SWEETA[®]
SENSE. RULE. TECHNOLOGY.

SWEETA

喜威達企業股份有限公司



Switches
Receptacles
Circuit Breakers



SENSE. RULE. TECHNOLOGY.

SWEETA[®]
SENSE. RULE. TECHNOLOGY.

喜威達企業股份有限公司
SWEETA PRODUCTS CORPORATION

總公司 / Head Office

Add : 23552 台北縣中和市中正路799號1樓
1F, No. 799, Chung Cheng Rd., Chung Ho City, Taipei Hsien, Taiwan 23552 R.O.C.
Tel : 886-2-2226-8001(REP.) **Fax :** 886-2-2226-8002 · 886-2-2226-8170
http : //www.sweeta.com **E-mail :** sweeta.tw@msa.hinet.net

工廠 / Factory

Add : 廣東省東莞市石碣鎮桔洲第三工業區
Juzhou Community, Shijie Town, Dongguan City, Guangdong Province, China.



INDEX



AC SOCKET	2
CIRCUIT BREAKER	9
DC JACK	10
DC JACK / IRIS JACK	12
POTO JACK / USB CONNECTORS / MODULAR JACK	13
DIGITAL SWITCH	14
DIP SWITCH	15
EMI FILTER	17
FUSE HOLDER / FUSE	18
HOOK SWITCH	20
KEY SWITCH / KEY SWITCH CAP	21
MICRO SWITCH / SEALED MICRO SWITCH (IP67)	22
MINI MICRO SWITCH	25
MINI PUSH SWITCH / CAP FOR TACT SWITCH	26
MINI SLIDE SWITCH	27
MINI SLIDE SWITCH / SEALED SWITCH (IP67)	29
MINI SWITCH	30
PLUG ADAPTOR	34
POWER CORD / USB CORD	36
PUSH SWITCH / IP67	41
RECEPTACLE	46
ROCKER SWITCH	49
ROCKER SWITCH SINGLE POLE	50
ROCKER SWITCH DOUBLE POLE / IP66	53
SENSOR SWITCH / DETECTOR SWITCH / PUSH & LEVER SWITCH	56
SLIDE SWITCH / TACT SWITCH WITH LED	57
TACT SWITCH / DOUBLE ACTION / SEALED TACT SWITCH / SHUTTER SWITCH	61
TERMINAL BLOCK	66
TIMER	68
TOGGLE SWITCH / CAP	69
VOLTAGE SELECTOR SWITCH	70
REED SWITCH / THERMOSTAT / BALL-ROLLING SWITCH	72

REED SWITCH/THERMOSTAT/BALL-ROLLING SWITCH

REED SWITCH/THERMOSTAT/BALL-ROLLING SWITCH

MKA-14103



Reed Switch

Glass Length: 14.2 x Ø2.3 max
 Overall Length: 44.7 x Ø0.55max
 Max.Contact Voltage: 10W Max.
 Max.Switching Voltage: 100V DC
 Max.Switching Current: 0.5A
 Max.Curry Current: 1.0A
 Max.Contact Resistance: 100mΩ

GPS-11



Reed Switch


Max.Contact Voltage: 10W Max.
 Max.Switching Voltage: 100V DC
 Max.Switching Current: 0.5A
-GPS-11:
 Glass Length: 11.0 x Ø2.55 max
 Overall Length: 41.8 max
-GPS-11-SMD: SMD Type
 Glass Length: 11.0 max
 Overall Length: 16.4 max

T240 Series



Thermostat

16A 250V / 15A 125V AC
 Auto Reset & Manual Reset
 Flush Mounting
 Terminal Type:



SAT-411



Ball Vibration Switch

Ø4.0 mm Gold Plated Cover
 1mA 24V DC
 Taiwan Patent No. 122545
 -SAT-411:
 -SAT-411-2:
 -SAT-411-R2:

RI-90



Reed Switch


Glass Length: 15.0 x Ø2.54 max
 Overall Length: 50.56 x Ø0.6max
 Max.Contact Voltage: 5W Max.
 Max.Switching Voltage: AC 125V DC
 DC 175V DC
 Max.Switching Current: AC 0.5A/DC 0.7A
 Max.Curry Current: 2.5A
 Max.Contact Resistance: 100mΩ

T24B Series



Thermostat

16A 250V / 15A 125V AC
 Auto Reset & Manual Reset
 Surface Mounting
 Terminal Type:




T24U Series



Thermostat

16A 250V / 15A 125V AC
 Auto Reset & Manual Reset
 Flush Mounting
 Terminal Type:



SBT-514



Ball Vibration Switch

Ø5.2 mm Nickel Plated Cover
 1mA 24V DC
 Taiwan Patent No. 122545
 -SBT-514:
 -SBT-514-2:

V10K



Reed Switch


Glass Length: 53.3 x Ø5.3 max
 Overall Length: 81.8 x Ø0.5max
 Max.Contact Voltage: 50W Max.
 Max.Switching Voltage: 10000V DC
 Max.Switching Current: 3.0A
 Max.Curry Current: 4.0A
 Max.Contact Resistance: 100mΩ

T24H,R Series



Thermostat

16A 250V / 15A 125V AC
 Auto Reset & Manual Reset
 Surface Mounting
 Terminal Type:




H2 Series



Thermostat (Ceramic Case)

16A 250V / 15A 125V AC
 Auto Reset & Manual Reset
 Surface Mounting & Flush Mounting
 Terminal Type:



BALL-ROLLING SWITCH



Tilt Sensor Switch
Vibration Sensor Switch
Optical Roll Ball Sensor Switch
Safety Sensor Switch

About SWEETA

Established in 1995, **SWEETA** is a professional manufacturer of all kinds of switches, AC sockets, as well as circuit breakers. Most of our products have been certified to meet international safety standards such as UL, CSA, VDE and others.

We are continuously developing new products to catch up with the ever-changing market demands. We do accept OEM projects. Excellent quality products, competitive prices, prompt delivery and royal service are guaranteed. At present, we are extending our business to Europe, US, Asia, Far East countries.

Quality Policy

To Customer Policy:

We regard the customers' satisfaction as our pride and honor.

Comprehensive Quality Control:

Our strict and comprehensive QC process guarantees the most reliable products.

High Standards:

Be it in the process of material selection or during product manufacturing, we are doing it with unremitting innovation and improvement in order to achieve the highest international standards.

