







UL, cUL 5A 125/250 VAC - 6000 cycles (Temp:120°C)
 ENEC 14 6A 250 VAC, μ T120, 10000 cycles with bare terminal
 with wire 6A 250VAC μ T70, 10000 Cycles

ORDERING CHARACTERISTICS

SWITCH TYPE	PART SUFFIX	OF Max. (gf)	OP (mm)	PT Max. (mm)	OT Min. (mm)	MD Max. (mm)	FP Max. (mm)	RF Min. (gf)
SSW-05S-00□□-□□□□□□-Z		203	8.4 ±0.3	1.2	0.6	0.2	9.9	50
SSW-05S-01□□-□□□□□□-Z		82	8.8 ±1.1	4.3	0.9	0.6	12.0	16
SSW-05S-02□□-□□□□□□-Z		66	8.8 ±1.2	4.8	1.0	0.7	12.4	13
SSW-05S-03□□-□□□□□□-Z		54	8.8 ±1.6	6.3	1.6	0.9	13.5	11
SSW-05S-04□□-□□□□□□-Z		68	10.7 ±1.2	4.6	1.0	0.65	14.1	14
SSW-05S-05□□-□□□□□□-Z		72	14.5 ±1.1	4.3	0.9	0.6	17.7	15